Materia
Material Safety
Data Sheet
Sheet

Hi-Yield® Dusting Wettable Sulfur

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Name: Voluntary Purchasing Groups, Inc.	Box 460, Bonham, TX 75418		
Emergency Telephone: (903) 583-5501 or (800) 424-9300 (Chemtrec)			
For Additional Information Contact: Product Manager or Chemtrec	Date Prepared:03-14-03		
Common Name (Used on Label): Hi-Yield® Dusting Wettable Sulfur	Chemical Family: Sulfur		
Chemical Name: Elemental Sulfur	Formula: Not determined		
Trade Name & Synonyms: Hi-Yield® Dusting Wettable Sulfur EPA # 7401-188-34911			

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENT	CAS NUMBER	% (TYPICAL)	TLV (UNITS)	PEL (UNITS)
Sulfur(nuisance dust)	7704-34-9	Proprietary	10 mg/m3	15 mg/m3

PEL: Permissible Exposure Limit established by the Occupational Safety and Health Administration.

TLV: Threshold Limit Value recommended by the American Conference of Governmental Industrial Hygienists.

SECTION 3 - PHYSICAL DATA

BOILING POINT (°F)	SPECIFIC GRAVITY (H ₂ O=1)		VAPOR PRESSURE (mm Hg)		
Not established	2.07				Not established
PERCENT VOLATILE BY VOLUME	(%)	VAPOR DE	NSITY (AIR=1)	EVAP(DRATION RATE (ethyl ether=1)
Not established	Not establish		hed	Not established	
SOLUBILITY IN WATER		REACTIVITY IN WATER			
Insoluble		Does not apply	,		
APPEARANCE AND ODOR					
Powder, sulfur odor.					

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT (°F)	FLAMMABLE LIMITS IN AIR (% by	volume)		
207 degrees C	Lower: 35 g/m3 Upper: 1400 g/m3	•		
EXTINGUISHING MEDIA	AUTO IGN	IITION TEMPERATURE		
Water fog, carbon dioxide	232 degre	es C		
UNUSUAL FIRE AND EXPLOSION HAZARDS				
Avoid overheating and ignition sources; dusts can from explosive mixtures with air.				
SPECIAL FIRE FIGHTING PROCEDURES				
Use a self-contained breathing apparatus.				

Product Name: Hi-Yield® Dusting Wettable Sulfur	ID Number:	Page: 1

SECTION 5 - HEALTH INFORMATION

DDIMADY DOLLTES OF EVDOSUDE						
	E AND TARGET ORGANS					
Eyes, skin, upper respiratory tract, ga						
SIGNS AND SYMPTOMS OF EXPO	SURE					
(1) ACUTE OVEREXPOSURE						
	SKIN CONTACT: Repeated contact					
	of the respiratory tract. INGESTION:	May cause irritation.				
(2) CHRONIC OVEREXPOSURE						
Not determined						
MEDICAL CONDITIONS GENERALI	LY AGGRAVATED BY EXPOSURE					
Not determined						
CHEMICAL/COMPONENT LISTED A	AS CARCINOGEN OR POTENTIAL CA	RCINOGEN				
None						
NTP	IARC	OSHA				
☐ YES ☒ NO	☐ YES ⊠ NO	☐ YES ⊠ NO				
OTHER EXPOSURE LIMITS						
None determined						
EMERGENCY AND FIRST AID PRO						
	r for 15 minutes. Seek medical a					
		nedical attention if irritation persists.				
		victim to fresh air, administer artificial				
respiration if not breathing and seek	medical attention immediately.					
	SECTION 6 - REACTIVITY DATA					
	SECTION 6 - REACTIVITY DATA					
STABILITY CONDI	SECTION 6 - REACTIVITY DATA TIONS TO AVOID					
☐ Unstable ☐ Stable Oxidize	TIONS TO AVOID ers, heat.					
☐ Unstable ☐ Stable ☐ Oxidize INCOMPATIBILITY (Materials to Avo	TIONS TO AVOID ers, heat. iid)	ides.				
☐ Unstable ☐ Stable ☐ Oxidize INCOMPATIBILITY (Materials to Avo	TIONS TO AVOID ers, heat. oid) ees, nitrates, charcoal, metals, and carb	ides.				
☐ Unstable ☐ Stable ☐ Oxidized INCOMPATIBILITY (Materials to Avoid Oxidizers, also separate form chlorate HAZARDOUS DECOMPOSITION PROPERTY OF THE PROPERTY OF	TIONS TO AVOID ers, heat. oid) ees, nitrates, charcoal, metals, and carb					
☐ Unstable ☐ Stable ☐ Oxidized INCOMPATIBILITY (Materials to Avoid Oxidizers, also separate form chlorate HAZARDOUS DECOMPOSITION PROPERTY OF THE PROPERTY OF	TIONS TO AVOID ers, heat. bid) ees, nitrates, charcoal, metals, and carb RODUCTS					
☐ Unstable ☐ Stable ☐ Oxidized INCOMPATIBILITY (Materials to Aveous Oxidizers, also separate form chlorated HAZARDOUS DECOMPOSITION PROPROSITION PR	TIONS TO AVOID ers, heat. bid) ees, nitrates, charcoal, metals, and carb RODUCTS					
☐ Unstable ☐ Stable Oxidized INCOMPATIBILITY (Materials to Avoid Oxidizers, also separate form chlorated HAZARDOUS DECOMPOSITION Proposition of Stable Oxides of Sulful Control of the Incompanies of Stable Oxides of Sulful Control of the Incompanies of Stable Oxides of Sulful Control of the Incompanies of Stable Oxides of Stable Oxides of Stable Oxides of Stable Oxides of Stable Oxidized Incompanies	TIONS TO AVOID ers, heat. oid) ees, nitrates, charcoal, metals, and carb RODUCTS ur including sulfur dioxide and sulfur trio CONDITIONS TO AVOID					
☐ Unstable ☐ Stable Oxidized INCOMPATIBILITY (Materials to Avoid Oxidizers, also separate form chlorated HAZARDOUS DECOMPOSITION PROPERTIES OF SURFICIAL PROPERTIES OF SURFICIAL PROPERTIES OXIGINATED IN THE PROPERTIES O	TIONS TO AVOID ers, heat. oid) ees, nitrates, charcoal, metals, and carb RODUCTS ur including sulfur dioxide and sulfur trio CONDITIONS TO AVOID					
☐ Unstable ☑ Stable Oxidized INCOMPATIBILITY (Materials to Aveous Oxidizers, also separate form chlorated HAZARDOUS DECOMPOSITION PROPROSITION PROPROSITION PROPROSITION WILLIAM OF THE PROPROSITION ■ May Occur ☑ Will Not occur	TIONS TO AVOID ers, heat. oid) ees, nitrates, charcoal, metals, and carb RODUCTS or including sulfur dioxide and sulfur trio CONDITIONS TO AVOID Not determined	xide, Hydrogen sulfide formation may				
☐ Unstable ☑ Stable Oxidized INCOMPATIBILITY (Materials to Aveous Oxidizers, also separate form chlorated HAZARDOUS DECOMPOSITION PROPROSITION PROPROSITION PROPROSITION WILLIAM OF THE PROPROSITION ■ May Occur ☑ Will Not occur	TIONS TO AVOID ers, heat. oid) ees, nitrates, charcoal, metals, and carb RODUCTS ur including sulfur dioxide and sulfur trio CONDITIONS TO AVOID	xide, Hydrogen sulfide formation may				
☐ Unstable ☐ Stable ☐ Oxidizers INCOMPATIBILITY (Materials to Avoid Oxidizers, also separate form chlorated HAZARDOUS DECOMPOSITION Property of the Upon oxidation will for oxides of sulfuralso occur. HAZARDOUS POLYMERIZATION ☐ May Occur ☐ Will Not occur	TIONS TO AVOID ers, heat. bid) ees, nitrates, charcoal, metals, and carb RODUCTS or including sulfur dioxide and sulfur trio CONDITIONS TO AVOID Not determined CTION 7 - SPILL OR LEAK PROCEDI	xide, Hydrogen sulfide formation may				
□ Unstable ☑ Stable Oxidized INCOMPATIBILITY (Materials to Avoid Oxidizers, also separate form chlorated HAZARDOUS DECOMPOSITION Properties of Sulful also occur. HAZARDOUS POLYMERIZATION □ May Occur ☑ Will Not occur	TIONS TO AVOID ers, heat. bid) ees, nitrates, charcoal, metals, and carb RODUCTS or including sulfur dioxide and sulfur trio CONDITIONS TO AVOID Not determined CTION 7 - SPILL OR LEAK PROCEDITIONS TO SPILLED	xide, Hydrogen sulfide formation may JRES				
□ Unstable ☑ Stable Oxidized INCOMPATIBILITY (Materials to Avoid Oxidizers, also separate form chlorated HAZARDOUS DECOMPOSITION Properties of Sulful also occur. HAZARDOUS POLYMERIZATION □ May Occur ☑ Will Not occur SE	TIONS TO AVOID ers, heat. bid) ees, nitrates, charcoal, metals, and carb RODUCTS or including sulfur dioxide and sulfur trio CONDITIONS TO AVOID Not determined CTION 7 - SPILL OR LEAK PROCEDI	xide, Hydrogen sulfide formation may JRES				
□ Unstable ☑ Stable Oxidized INCOMPATIBILITY (Materials to Avoid Oxidizers, also separate form chlorated HAZARDOUS DECOMPOSITION Properties of Sulful also occur. HAZARDOUS POLYMERIZATION □ May Occur ☑ Will Not occur SEE STEPS TO BE TAKEN IN CASE MAY Keep dust levels at a minimum when WASTE DISPOSAL METHOD	TIONS TO AVOID ers, heat. oid) ees, nitrates, charcoal, metals, and carb RODUCTS or including sulfur dioxide and sulfur trio CONDITIONS TO AVOID Not determined CTION 7 - SPILL OR LEAK PROCEDI TERIAL IS LEAKED OR SPILLED cleaning up and keep away from heat	xide, Hydrogen sulfide formation may JRES				
□ Unstable ☑ Stable Oxidized INCOMPATIBILITY (Materials to Avoid Oxidizers, also separate form chlorated HAZARDOUS DECOMPOSITION Properties of Sulful also occur. HAZARDOUS POLYMERIZATION □ May Occur ☑ Will Not occur SE	TIONS TO AVOID ers, heat. oid) ees, nitrates, charcoal, metals, and carb RODUCTS or including sulfur dioxide and sulfur trio CONDITIONS TO AVOID Not determined CTION 7 - SPILL OR LEAK PROCEDI TERIAL IS LEAKED OR SPILLED cleaning up and keep away from heat	xide, Hydrogen sulfide formation may JRES				
□ Unstable ☑ Stable Oxidized INCOMPATIBILITY (Materials to Avon Oxidizers, also separate form chlorated HAZARDOUS DECOMPOSITION Programmer of the Upon oxidation will for oxides of sulful also occur. HAZARDOUS POLYMERIZATION □ May Occur ☑ Will Not occur SEE STEPS TO BE TAKEN IN CASE MAY Keep dust levels at a minimum when WASTE DISPOSAL METHOD	TIONS TO AVOID ers, heat. oid) ees, nitrates, charcoal, metals, and carb RODUCTS or including sulfur dioxide and sulfur trio CONDITIONS TO AVOID Not determined CTION 7 - SPILL OR LEAK PROCEDI TERIAL IS LEAKED OR SPILLED cleaning up and keep away from heat	xide, Hydrogen sulfide formation may JRES				

Product Name: Hi-Yield® Dusting	g Wettable Sulfur	ID Number:	Page: 2

SECTION 8 - PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION

No required under conditions of normal intended use. Use a NIOSH approved respirator if exposure is above 10mg/m3 nuisance dust.

VENTILATION

Use in a well-ventilated area.

PROTECTIVE GLOVES

If skin contact is likely to occur.

EYE PROTECTION

Safety goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

None determined

SECTION 9 - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING & STORING

Keep container closed when not in use and store in a cool dry area.

OTHER PRECAUTIONS

None determined

SECTION 10 - OTHER INFORMATION

The information contained within was obtained from authoritative sources and is believed to be accurate for the manner in which the product is intended to be used. Other uses could result in ramifications, which are not included within this document.